

经济型全电动堆垛车 Economic electric stacker



- ◆配置大功率，高性能提升泵站：货物起升平衡有力，性价比高。
- ◆电机驱动系统：体积小，损坏小，效率高。
- ◆侧驾驱动设计：转弯半径小，适合狭小空间作业。
- ◆操作手柄：符合人体工程学原理，操作舒适。
- ◆龟速开关：精准控制速度。
- ◆ High-power, high-performance lift motor: powerful cargo lifting, cost-effective.
- ◆ DC motor drive system: smaller size, high efficiency.
- ◆ Side-driven design: smaller turning radius, suitable for operation in confined space.
- ◆ Operation handle: ergonomics, comfortable operation, increased work efficiency.
- ◆ Maintenance free battery and internal charger: easy for maintenance, easy to charge.
- ◆ Optional: Adjustable baseleg or straddle.

参数项目Parameters / 型号Model		CLE-10
额定载荷 Capacity	kg	1000
载荷中心距 Load Center	mm	500
起升高度 Max height	mm	2000/2500/3000
门架作业时整车最大高度 Overall extended height	mm	2415/2915/3415
门架缩回时整车静止高度 Overall collapsed height	mm	1580/1830/2080
货叉外宽 Fork width	mm	540/680
货叉尺寸 Fork size (L*W*T)	mm	1150 (1220)*160*55
货叉最低高度 Min. height	mm	90
整车宽度 Overall width	mm	820
整车长度 Overall length	mm	1950 (2020)
转弯半径 Turning radius	mm	1360
最大行驶速度，满载/空载 Max travel speed, laden/ unladen	Km/h	3/4.5
最大起升速度，满载/空载 Max lift speed, laden/ unladen	mm/s	80/100
最大下降速度，满载/空载 Max lowering speed, laden/ unladen	mm/s	90/120
爬坡度，满载/空载 Max Gradient performance, laden/unladen	%	5/7
驱动轮 Rear wheel	mm	PU φ210*70
承重轮 Front wheel	mm	PA/PU φ80*70
平衡轮 Balance wheel	mm	PA/PU φ180*50
驱动电机 Driving motor	Kw	DC0.75
起升电机 Lift motor	Kw	DC1.5
电池容量 Battery capacity	V/A	12V*2/60Ah
自重 Weight	Kg	440/490/535
电池重量 Battery weight	Kg	45

半电动堆垛车 Semi-electric Stacker

- ◆大功率电机：升降平稳，性价比高。
- ◆门架导轮，链轮和轴承都采用大叉车设计：提升工作效率，减少产品损坏。
- ◆带刹车：稳定作业，增加作业安全性。
- ◆组合式货叉及门架：降低物流成本，维修更方便。
- ◆紧急停车装置：提高操作人员安全性。
- ◆可调节前腿（可选）。
- ◆ High power lift motor: smooth lifting and lowering, cost-effective.
- ◆ Forklift mast wheel, sprocket, chain, and bearings: increased work efficiency, eliminating costly repair.
- ◆ Parking brake: steady opeartion, ensured personnel safety.
- ◆ Removable masts and forks: lowering logistics costs, easy to repair and maintenance.
- ◆ Emergency stop: improves operator's safety.
- ◆ Optional: adjustable baseleg (or straddle).



参数项目Parameters/ 型号Model		AKCDSD10	AKCDSD20	AKCDSD30
额定载荷 Capacity	Kg	1000	2000	3000
载荷中心 Load center	mm	500	500	500
转弯半径 Turning radius	mm	1350	1350	1350
起升高度 Max. lift height	mm	1600/2000/2500	1600/2000/2500	1600
货叉最低高度 Min. height	mm	80	80	80
货叉尺寸 Fork size	mm	1070×160	1070×160	1070×160
货叉外宽 Fork width	mm	680	680	680
货叉最小离地间距 Fork min. height	mm	25	25	25
整车宽度 Overall width	mm	780	780	780
整车长度 Overall length	mm	1655	1655	1655
整车高度 Overall height	mm	2055/1575/1825	2055/1575/1825	2055
蓄电池容量 Battery capacity	V/A	12V/105 Ah	12V/105 Ah	12V/105 Ah
充电器 Charger	V/A	DC12V/15A(内置Internal)	DC12V/15A(内置Internal)	DC12V/15A(内置Internal)
驾驶方式 Driving Method		站立式Stand	站立式Stand	站立式Stand
自重 Weight	Kg	350-420	420-500	520

手动插腿式液压叉车 Hand Hydraulic Stacker



- ◆C型钢门架：下降平稳，安全牢固。
- ◆串杆式货叉：轻松调节，适合不同场所作业，一车多用。
- ◆八字后腿：转向更灵活，更安全。
- ◆货叉最低高度80mm：适用于多种规格托盘。
- ◆控制手把：一键操作所有功能。

◆C-channel structure: precise lifting and lowering, not easy to deformation, safety.

◆Adjustable fork: suitable for different workplaces, a multi-purpose truck.

◆Angled wheel design: easy to maneuver, increased work efficiency.

◆Minimum fork height 80mm: suitable for different sizes of pallets.

◆Handle: fingertip control of all functions.

CTY C型钢
(“C” Type Steel)



加宽型堆垛车
Widen Stacker



工模车
Mould Stacker



多功能升高车
Multifunction Stacker

参数项目Parameters / 型号Model		CTY1.0	CTY2.0
额定载荷 Capacity	Kg	1000	2000
起升高度 Max.lift height	mm	1600/2000/2500	1600/2000
货叉最低高度 Min. height	mm	80-100	80-100
货叉长度 Fork length	mm	800	900
起升速度 Lifting speed	mm/s	24	18
下降速度 Lowering speed		可控Controllable	
整车宽度 Overall width	mm	750	770
整车长度 Overall length	mm	1270	1370
整车高度 Overall height	mm	1970/1580/1830	2020/1580
后轮尺寸 Diameter of the rear wheel	mm	φ 180×50	
前轮尺寸 Diameter of the front wheel	mm	φ 80×60	φ 80×70
自重 Weight	Kg	162-240	195-235

手动液压托盘搬运车 – 异型车 Hand pallet truck – custom made



◆ 加长型
Lengthen Pallet Truck



◆ 缩短型
Shorten Pallet Truck



◆ 加宽型
Widen Pallet Truck



◆ 设备搬运车
Equipment Pallet Truck



◆ 纸筒车
Roll Paper Truck



◆ 槽钢拖纸车
Channel steel Roll Paper Truck

液压油桶搬运车 Hydraulic Drum Truck



前移式叉车（小前移）
Electric reach stacker



焊枪自动清理机 Automatic robotic torch cleaning station



前移式叉车
Electric reach forklift



外置/内置汽车尾板 External/Internal Tail Lift



参数项目Parameters 型号Model		DC-WB
尾板宽 Tail lift width	mm	1600-2500
尾板高 Tail lift height	mm	1650-2000
额定载重 Max. lifting capacity	kg	1000-3000
自身重量 Net Weight	kg	350-580
面板工作角度 Panel working angle	°	5-9
电机动力 Generator voltage	V	12V/24V
电机功率 Generator power	kw	2-3kw
最小车尾长度 The minimum length of the tail	mm	720-1000
适用厢地高度 Applicable car height	mm	650-1550
升降速度 Average lifting speed	mm/sec	50-80
油料 Oil		抗磨液压油 Anti-wear hydraulic oil

- ◆ 液压系统可全自动操作，适合安装于各种货车。
- ◆ 采用全封闭式花纹钢质面板，坚固，平稳，美观大方，客户可根据需求选择内置或外置尾板。
- ◆ Automatic operation of hydraulic system is suitable for installation of any type of truck.
- ◆ Fully closed pattern solid steel panel can be stalled inside or outside of the gate. Customized design is welcome.

移动式液压升降平台 Mobile Scissor lift



参数项目Parameters 型号Model		SJY0.3-3	SJY0.2-4	SJY0.5-4.5	SJY0.3-6	SJY0.5-6	SJY0.3-9	SJY0.5-9
额定载荷 Capacity	Kg	300	200	500	300	500	300	500
最大高度 Max.lift height	mm	3000	4000	4500	6000	6000	9000	9000
最低高度 Min. height	mm	770	850	980	950	950	1500	1600
台面尺寸 Platform size	mm	1300*770	1500*700	1300*850	1780*840	1780*840	2150*1000	2150*1000
电机功率 Motor power	kw	0.75	0.75	0.75	1.1	1.5	1.5	2.2
电源Power	V/Hz	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz	380V/50Hz

选配 Optional: 电源 Power: AC220V or DC24V 手动/电动Manual/Electric

产品技术解释权归广东亚克迪智能物流科技有限公司
AKODI reserves the right to interpret the product
models and technical specifications.



Website



亚克迪叉车

地址：广东省鹤山市雅瑶镇昆东工业区1号 ADD:No.1 KunDong Industrial Zone, YaYao, Heshan, GuangDong, China

电话(Tel): +86 -750-8538289 8538228 8538008 传真(Fax): +86-750-8538291 8538209

全国服务热线 (customer service): 4001-102-098

Http: //www.akodiforklift.com, www.jh-akodi.com

E-mail:sales @akodiforklift.com, akodi@jh-akodi.com